

GENEX E

3F

Fluorosynthetic Foam AFFF

PERFORMANCE & WARRANTY

GENEX E meets international requirements
EN 1568-3: Class IB
ISO 7203-1
ICAO Level B
EN3

GENEX E can be used with tap water, brackish water and sea water.

GENEX E contains corrosion inhibitors.

GENEX E is designed to work effectively in extinguishers for B rating.

GENEX E has a 10 years warranty in its original packaging and at storage temperatures -30°C/+60°C.

PHYSICAL DATA

	GENEX E		
	ESC	3E	6E
Appearance / Colour	Brown	Yellow liquid	
Concentration of use	1 - 3%	3%	6%
Specific Gravity at 20°C (Kg/dm ³)	1.05	1.02	1.01
Viscosity at 20°C (cStokes)	12	7	2
Freezing point	-30°C	-8°C	-5°C
Ph at 20°C		8	
Sediment after ageing		<0.1%	
Surface tension (mN/m)		16	
Interfacial tension (mN/m)	2		3

FOAM QUALITY

Low Expansion		8	
Drainage time 25% / 50%		3 min. / 5 min.	



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk