

PENTSPRAY SF

3F

SF

Class A Extinguisher Additive Fluorine Free Solvent Free

PHYSICAL DATA

Appearance / Colour	Orange liquid
Concentration of use	5 - 17%
Specific Gravity at 20°C (Kg/dm ³)	1.20
Viscosity at 20°C (cStokes)	5
Freezing point	-14°C
Ph at 20°C	8
Sediments after ageing	<0.1%

EXTINGUISHER - *Typical rating:*

3 Litre	8A – 13A
6 Litre	21A – 27A
9 Litre	27A – 34A

PERFORMANCE & WARRANTY

PENTSPRAY SF meets EN3 European standard as a Class A water additive.

PENTSPRAY SF can be used either as a concentrate to be diluted down -10% to 17%- and mixed with class B additives, or as a premixed solution, to enhance the performance on carbonaceous solid fuels.

The rating attained to EN3 will be determined by both the type of nozzle and discharge time.

The extinguisher size to be used and the EN3 wooden crib size will determine the concentration of use.

PENTSPRAY SF has a 5 years warranty in its original packaging and at storage temperatures 0°C / +60°C.

PENTSPRAY SF has a 5 years warranty as a premix solution, contained and sealed in a lined extinguisher unit.



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk